THREELINE
SPAIN

LUVI
LV27W
Street light bulb LED 27W



HIGH EFFICIENCY
153 lm/W

PRO

5 GARANTÍA

HQ HIGH QUALITY

LG

www.threeline.es


THREELINE
SPAIN

SPECIFICATIONS · PRODUCT DATA


Electrical data	
Input	110 ~ 240 Vac
Mains frequency	50/60Hz
Power	27 W
Fower factor	> 0,95
LEDs n°	153
LED power	0,18 W
IEC protection class	Class II
Connector	E27/E40
Photometric data	
Luminous efficiency	153 lm/W
CRI (Ra)	> 80
Luminous lux (Nominal / Real) CCT	4590 lm · 4125 lm · 6500K · BF 4536lm · 4048lm · 4000K · BN
Luminous intensity	403 cd
SDCM Standard deviation colour adjustment	<3
Degree of opening	360°
Working Temp.	-30°C ~ +60°C
Switchovers n°	30.000
Certifications	CE, RoHS
Energy efficiency	A++
Working life	50.000 h (L80B10)
Materials and physical characteristics	
Body	PC
Diffuser	PC
Measurements in mm (length x width x height)	205,7 X Ø93,2 (E40)
Weight (g)	750
Characteristics	
IP Rating	IP64
IK Rating	05
Options	
Dimming option	No
Emergency kit option	No
Sensor movement option	No
Packaging	
Packaging measurements	510 X 380 X 500
Packaging weight (kg)	18,9
Units (units/box)	24 units

Measurements in mm

Conector E27




Conector E40



Optics

Beam angle 360°

H (m)	Diameter (m)	Emax (lx)
1	0.2	201
2	0.4	50
3	0.6	22
4	0.8	13



C/Pulimentadores,1 · 02640 Almansa (Albacete) · T. 967 318 293 · F. 96 340 002
tl@threeline.es · www.threeline.es

THREELINE
SPAIN

References

		W				CCT	CRI
LV27WE27BF	E27	27 W	4590 lm	4125 lm	360°	BF: 6500K	> 80
LV27WE27BN	E27	27 W	4536 lm	4048 lm	360°	BN: 4000K	> 80
LV27WE40BF	E40	27 W	4590 lm	4125 lm	360°	BF: 6500K	> 80
LV27WE40BN	E40	27 W	4536 lm	4048 lm	360°	BN: 4000K	> 80



Rev 2102

C/Pulimentadores,1 · 02640 Almansa (Albacete) · T. 967 318 293 · F. 96 340 002
tl@threeline.es · www.threeline.es