THREELINE
SPAIN

LUVI
LV54W
Street light bulb LED 54W



HIGH EFFICIENCY
155 lm/W

PRO

5 GARANTÍA

HQ HIGH QUALITY

LG

www.threeline.es


THREELINE
SPAIN

SPECIFICATIONS · PRODUCT DATA


Electrical data	
Input	110 ~ 240 Vac
Mains frequency	50/60Hz
Power	54 W
Fower factor	> 0,95
LEDs n°	306
LED power	0,18 W
IEC protection class	Class II
Connector	E27/E40
Photometric data	
Luminous efficiency	155 lm/W
CRI (Ra)	> 80
Luminous lux (Nominal / Real) CCT	9180 lm · 8375 lm · 6500K · BF 9072lm · 8230lm · 4000K · BN
Luminous intensity	851 cd
SDCM Standard deviation colour adjustment	<3
Degree of opening	360°
Working Temp.	-30°C ~ +60°C
Switchovers n°	30.000
Certifications	CE, RoHS
Energy efficiency	A++
Working life	50.000 h (L80B10)
Materials and physical characteristics	
Body	PC
Diffuser	PC
Measurements in mm (diameter x height)	266,7 X Ø93,2 (E40)
Weight (g)	900
Characteristics	
IP Rating	IP64
IK Rating	05
Options	
Dimming option	No
Emergency kit option	No
Sensor movement option	No
Packaging	
Packaging measurements	510 X 380 X 620
Packaging weight (kg)	24,3
Units (units/box)	24 units

Measurements in mm

Conector E27




Conector E40



Optics

Beam angle 360°

H (m)	Diameter (m)	Emax (lx)
1	0.2	441
2	0.4	110
3	0.6	49
4	0.8	28



C/Pulimentadores,1 · 02640 Almansa (Albacete) · T. 967 318 293 · F. 96 340 002
tl@threeline.es · www.threeline.es

THREELINE
SPAIN

References

		W				CCT	CRI
LV54WE27BF	E27	54 W	9180 lm	8375 lm	360°	BF: 6500K	> 80
LV54WE27BN	E27	54 W	9072 lm	8230 lm	360°	BN: 4000K	> 80
LV54WE40BF	E40	54 W	9180 lm	8375 lm	360°	BF: 6500K	> 80
LV54WE40BN	E40	54 W	9072 lm	8230 lm	360°	BN: 4000K	> 80



Rev 2102

C/Pulimentadores,1 · 02640 Almansa (Albacete) · T. 967 318 293 · F. 96 340 002
tl@threeline.es · www.threeline.es